

Segment Gasket Adhesive - SOLVEN-BASED

Material	CONTACT ADHESIVE	Date	10.02.2014
		Revision Date	31.07.2015
Form Number	FR.02.TL-00002	Version	2

GENERAL PROPERTIES

PRODUCT DEFINITION	: Polychloroprene-based general-purpose contact adhesive.
VISCOSITY (cp)	: 2000 - 2500
DENSITY	: 1,2
COLOR	: Light Yellow
APPLY TEMPERATURE (°C)	: Room temperature
DRY TIME (min.)	: 15-20
WEIGHT (kg)	: 20 KG. Barrel

STORAGE TEMPERATURE (°C): Store products exposed to temperatures between +10°C and +30°C. Before use, allow products stored in cold temperatures to warm up at room temperature for 24 hours. The shelf life is one year

APPLY METHOD : A smooth bonding can be achieved on all absorbent surfaces using a brush or roller. The surfaces to be bonded must be clean, dry, and sanded.

USE AREA : It is a multipurpose adhesive. It is a high-quality adhesive used in the automotive industry for ceiling and floor coverings, door seals and gaskets, bonding foam, fabric, and synthetic leather, as well as in the shoe, slipper, leather goods, and furniture industries. It is also used for bonding flooring materials and insulation coatings, and for superior bonding in concrete to rubber and concrete to plastic combinations.

WARNING : The adhesive should be thoroughly mixed before use and the container tightly sealed after application. The work area should be well-ventilated, no smoking should be allowed, and naked flames should be kept away.